



Key Features




Despertar HDMI

Per maximitzar l'experiència de l'usuari mentre utilitza vídeo extern dispositius com reproductors multimèdia, controladors de pantalla o PC, tots els nostres Els dispositius tenen la funció de despertador HDMI preparada per activar/desactivar el pantalla simplement connectant/desconnectant el cable HDMI.



Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



Pixel Shifting

Pixel Shifting is designed to be activated inside the SoC in order to prevent for potential risk of image sticking, caused by constant content. With this feature turned on, pixels on the screen will move in an interval while causing no interference of visual experience.




Scheduler

Digital Signage Monitor Software allows many important features such as Scheduler. Scheduler sets your display turn on/off time easily and lets you not to worry about the status of your displays in any time.



Tecnologia DAP (Dolby Audio Processing)

Les nostres pantalles ofereixen un rendiment sonor complet utilitzant l'última tecnologia DAP de Dolby. Amb incrustat Tecnologia DAP, s'aconsegueix un rendiment de so superior equalització intel·ligent d'àudio, millores de diàleg i envoltant barreja de so.



HDR10 & 4K HDMI @60Hz

Amb la compatibilitat HDR10, els clients poden garantir-ho tot el contingut destacat compleix les directrius HDR i arriba a un nivell superior qualitat d'imatge de la manera més clara i brillant possible. Diferent que molts productes del mercat, contingut 4K a través de HDMI La font és compatible a 60 Hz.

Mostra

Screen Size	55"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	400 cd/m²
Native Resolution	UHD: 3840 x 2160 - HDR10	Contrast Ratio (typical)	1300:1
Dynamic Contrast Ratio	40000:1	Panel Life Time (Min.)	30000 Hrs
Response Time (typical)	9 ms	Active Area (H x V)	1210 x 681 mm
Pixel Pitch (H x V)	0.315 x 0.315 mm	PPI (pixel per inch)	81
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07 B (10-bit)
Screen Treatment	3H	Haze Level	1%
Refresh Rate	60 Hz	Front Type	Ultra Narrow Bezel
Orientation	Horizontal	Operation Hours	16/7
Area of Usage	Indoor		

Sistema incorporat

Mainboard Model	17MB135VS
-----------------	-----------

E/S posteriors

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	4xHDMI2.0 (HDCP2.2), 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Mechanical

Product Dimensions (WxDxH)	1238 x 104 x 712 mm	Package Dimensions (WxDxH)	1369 x 165 x 874 mm
Product Weight	17.05 kg	Package Weight	21.65 kg
Vesa Mounting	400 x 200 mm - M6	Bezel Width	B:14 T:11 L/R:11 mm

Condicions ambientals

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

Poder

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Consum energètic

Typical	118 W	Maximum	180 W
Deep Standby	≤0.5 W		

Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock	Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance, IR Overlay Touch Compliance	Speaker	2 x 8 W

Accessoris

Standard

QSG, IB, Power Cord, Remote
Control, RC Battery, Mounting Kit,
Extension Brackets, IR Extender
Cable

Certificació

Safety

YES

EMC

YES

CE

YES