

IFXD65TH752P/3



Key Features




IFPD intel·ligent

L'ordre de veu amb el micròfon incrustat s'afegeix comoditat per a les activitats de l'aula. El sensor de proximitat activa l'IFPD quan una persona entra a l'habitació i després en tocar l'alimentació, el producte s'encén a l'instant.



Ràpid i fàcil d'arribar

Connecteu fàcilment ordinadors o altres dispositius a la part frontal. Entrades HDMI, tàctil i USB. Els altaveus frontals asseguren so clarament projectat dins l'entorn de l'aula.



Panell de cura dels ulls

Durant molt de temps, la sèrie IFX té un mode d'imatge especial anomenat "Cura dels ulls". Aquest mode d'imatge disminueix la llum blava i a més, no té parpelleig a la brillantor màxima.

Mostra

Screen Size	65"	Backlight Type	Direct-Type LED
Brightness (typical)	350 cd/m²	Native Resolution	UHD: 3840 x 2160 - HDR10
Contrast Ratio (typical)	1200:1	Dynamic Contrast Ratio	35000:1
Panel Life Time (Min.)	30000 Hrs	Response Time (typical)	8 ms
Active Area (H x V)	1428 x 804 mm	Pixel Pitch (H x V)	0.372 x 0.372 mm
PPI (pixel per inch)	68	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	1.07 B (10-bit)	Screen Treatment	3H
Haze Level	8%	Refresh Rate	60 Hz
Front Type	Black Super Narrow Bezel	Orientation	Horizontal
Operation Hours	16/7	Area of Usage	Indoor

Sistema incorporat

Mainboard Model	17MB135VS
-----------------	-----------

E/S posteriors

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	3xHDMI2.0, 2xUSB2.0, USB2.0(Internal), 1x MicroSD	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Toqueu Interactivitat

Type of Touch Technology	Infrared (IR) Technology	Continuous Touch Points	10 Points
Sensitivity	Any touch with finger, gloved hand or pointer	Connectivity	HID, TUIO, Flash
Compatibility	Windows®7, Windows®8, Windows®10, Vista, XP, Mac® OS, Linux, Android	Orientation	Landscape Support
Calibration	No need	Accuracy	90%
Reporting Rate	Up to 450 fps	Glass Type	Anti Glared (AG), 4mm tempered
Frame Rate	Up to 450 fps	Communication	USB2.0
Power Supply Mode	USB	Supply Voltage	DC 5V +/- 5%
Average Current	400 mA	Response Time	10 ms
Touch Accuracy	+/-2mm (over 90% area)	Touch Durability	Unlimited
HID Compatibility	Yes USB	Object Sizes for Touch	5 mm

Mechanical

Product Dimensions (WxDxH)	1513 x 139 x 975 mm	Package Dimensions (WxDxH)	1765 x 265 x 1187 mm
Product Weight	48 Kg	Package Weight	62 Kg
Vesa Mounting	400 x 400 mm	Bezel Width	B:129 T:41 L/R:41 mm

Condicions ambientals

Operating Temperature	+40°C / 0°C	Operating Humidity	90%
-----------------------	-------------	--------------------	-----

Poder

Power Supply	110 VAC - 240 VAC
--------------	-------------------

Consum energètic

Typical	TBD	Deep Standby	≤ 0.5W
---------	-----	--------------	--------

Features

Main Features	Proximity Sensor, Microphone, USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up	Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance	Speaker	2x12W

Accessoris

Standard	QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets
----------	---

Certificació

Safety	YES	EMC	YES
CE	YES	Reability Approval	YES