



Key Features



Embedded CMS

Embedded content management program which supports playback library, ready templates and scheduler. With its simple and intuitive menus and layout options, it is effective for small and medium enterprises to make easy content management.



Menu Lock

Allows user to enable/disable menu access in order to prevent displays settings in the public area. After initial installation, you can have additional security to your signage displays in the field by using menu lock feature.



Wireless Display

Using either Microsoft Wireless Display Adaptor or Android Screen Sharing functions on Windows and Android devices, you can mirror screen to the display using embedded wireless display capabilities without using any external devices or cables.



HDMI Wake Up

To maximize the user experience while using external video devices such as mediaplayers, display controllers or PCs, all our devices have HDMI Wakeup feature ready to turn on/off the display by simply plugging/unplugging the HDMI cable.



IP Streaming Support

Our processors in the displays make it easier to manage content through many devices. IP video streaming protocols such as RTSP/RTP/HLS and UDP Multicast are supported for real-time content streaming. So that, live broadcasts can be displayed in this way.



Detachable Logo

Detachable logo allows you to put the logo desired position. Either portrait or landscape mode your logo presented in a good placement. Also you can remove the logo if it is blocking you to use more screens together.

Bistaratztea

Screen Size	49"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	700 cd/m²
Native Resolution	1920 x 1080 (16:9) - FHD	Contrast Ratio (typical)	1000:1
Dynamic Contrast Ratio	70000:1	Panel Life Time (Min.)	50000 Hrs
Response Time (typical)	6 ms	Active Area (H x V)	1074 x 605 mm
Pixel Pitch (H x V)	0.5593 x 0.5593 mm	PPI (pixel per inch)	45
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	16.7 M (8-bit)
Screen Treatment	3H	Haze Level	1%
Refresh Rate	60 Hz	Front Type	Ultra Narrow Bezel
Orientation	Horizontal / Vertical	Operation Hours	24/7
Area of Usage	Indoor		

Sistema integratua

Mainboard Model	17MB135VS
-----------------	-----------

Atzeko I/Oak

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	4xHDMI2.0, 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Mechanical

Product Dimensions (WxDxH)	1102 x 104 x 635mm	Package Dimensions (WxDxH)	1215 x 165 x 775mm
Product Weight	12.80 kg	Package Weight	16.80 kg
Vesa Mounting	200 x 200 mm M6	Bezel Width	B:15 T:11 L/R:11 mm

Ingurumen Baldintzak

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

Boterea

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Energia-kontsumoa

Typical	95 W	Deep Standby	≤0.5 W
---------	------	--------------	--------

Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock	Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance, IR Overlay Touch Compliance	Speaker	2 x 8 W

Osagarria

Standard

QSG, IB, Power Cord, Remote
Control, RC Battery, Mounting Kit,
Extension Brackets, IR Extender
Cable

Ziurtapena

Safety

YES

EMC

YES

CE

YES