



Key Features



Abiarazi automatikoa

SoC softwarearen barruan HTML5-n oinarritutako edozein aplikazio esteka ematea erraztu dugu pantailara. Horren ondoren, pantaila emandako estekarekin hasiko da. Aplikazioa lineaz kanpoko edo lineako aplikazio bat izan daiteke, bezeroei beren aplikazioa exekutatzeko aukera emanez.



Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



Pixel-aldaketa

Pixel Shifting funtzioa aktibatu daiteke, eduki estatikoa denbora luzez bistaratzen denean irudiak itsasteko arriskua murrizteko. Ezaugarriak aldian-aldian pantailako irudia aldatzen du, ikusmen-esperientziaren interferentziarik eragin gabe.



Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



Eragiketa-denbora-laguntza

Serie honekin erabiltzen diren panel profesionalak eguneko 24 orduetan funtzionatzen dutela ziurtatu dute inolako arazorik gabe. Gure bezeroek gure pantailen kalitate gorena ezagutuko dute edozein eragiketarako mugarik gabe. Horren harira, serieak 700 Nitseko distiramaila ditu barruko ingurune distiratsuetarako egokiak.

Bistaratztea

Screen Size	55"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	700 cd/m²
Native Resolution	1920 x 1080 (16:9) - FHD	Contrast Ratio (typical)	1000:1
Dynamic Contrast Ratio	70000:1	Panel Life Time (Min.)	50000 Hrs
Response Time (typical)	6 ms	Active Area (H x V)	1210 x 681 mm
Pixel Pitch (H x V)	0.630 x 0.630 mm	PPI (pixel per inch)	40
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	16.7 M (8-bit)
Screen Treatment	3H	Haze Level	1%
Refresh Rate	60 Hz	Front Type	Ultra Narrow Bezel
Orientation	Horizontal / Vertical	Operation Hours	24/7
Area of Usage	Indoor		

Sistema integratua

Mainboard Model	17MB120DSR4-DSOPT6
-----------------	--------------------

Atzeko I/Oak

RGB Input	Dsub 15 PIN VGA CON., YPbPr	RGB Output	N/A
Video Input	2xHDMI2.0, 1xUSB3.0, 1xUSB2.0, 1xUSB2.0(USB Cover)	Video Output	HDMI2.0
Audio Input	LINE IN JACK	Audio Output	LINE OUT JACK
External Control	RS232(DSUB 9P), RJ12, Ethernet	External Sensor	N/A

Mechanical

Product Dimensions (WxDxH)	1238 x 104 x 712 mm	Package Dimensions (WxDxH)	1369 x 165 x 874 mm
Product Weight	17.1 kg	Package Weight	21.4 kg
Vesa Mounting	400 x 200 mm - M6	Bezel Width	B:14 T:11 L/R:11 mm

Ingurumen Baldintzak

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

Boterea

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Energia-kontsumoa

Typical	105 W	Deep Standby	≤0.5 W
---------	-------	--------------	--------

Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock	Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Herausnehmbares Netzkabel, Carrying slots, Detachable logo positioning, Internal usb cover, Kabelhalterung
Optional Features	OPS Compliance, IR Overlay Touch Compliance	Speaker	2 x 8 W

Osagarria

Standard

QSG, Garantiekarte,
Bedienungsanleitung,
Stromversorgungskabel,
Fernbedienung, Batterie,
Montageset

Ziurtapena

Safety

YES

EMC

YES

CE

YES