



## Key Features



### Optional OPS Support

All our products in this series have an optional OPS (Open Pluggable Standard) slot. OPS will empower your screens with enhanced processing power and ability to choose Windows or Android as your operating system to fit your specific application.



### Auto Launch

We have made it easy to give any HTML5-based application link to the display within the SoC software. Upon this, the display will start with the given link. The application can either be an offline or an online application, allowing the customers to execute their own application.



### Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



### Usb Security

This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



### Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



### Operation Time Support

Professional Panels used with this series are quality confirmed to operate 24 hours a day without any issues. Upon this, the series come with 500 Nits brightness levels suitable for medial indoor environment.

Bistaratztea

|                          |                    |                         |                                                    |
|--------------------------|--------------------|-------------------------|----------------------------------------------------|
| Screen Size              | 65"                | Backlight Type          | Edge-Type LED                                      |
| Brightness (typical)     | 500 cd/m²          | Native Resolution       | UHD: 3840 x 2160 - HDR10                           |
| Contrast Ratio (typical) | 1200:1             | Dynamic Contrast Ratio  | 50000:1                                            |
| Panel Life Time ( Min. ) | 50000 Hrs          | Response Time (typical) | 6 ms                                               |
| Active Area (H x V)      | 1428.5 x 803.5 mm  | Pixel Pitch (H x V)     | 0.372 x 0.372 mm                                   |
| PPI (pixel per inch)     | 68                 | Viewing Angle           | 178° Vert., 178° Hor.<br>(89U/89D/89L/89R) @ CR>10 |
| Color Value              | 1.07 B (10-bit)    | Screen Treatment        | 2H                                                 |
| Haze Level               | 3%                 | Refresh Rate            | 60 Hz                                              |
| Front Type               | Ultra Narrow Bezel | Orientation             | Horizontal / Vertical                              |
| Operation Hours          | 24/7               | Area of Usage           | Indoor                                             |

Sistema integratua

|                 |           |
|-----------------|-----------|
| Mainboard Model | 17MB135VS |
|-----------------|-----------|

Atzeko I/Oak

|                  |                                                |                 |                        |
|------------------|------------------------------------------------|-----------------|------------------------|
| RGB Input        | VGA(DE-15F)                                    | RGB Output      | N/A                    |
| Video Input      | 4xHDMI2.0, DP1.2a, 2xUSB2.0                    | Video Output    | HDMI2.0, DP1.2a        |
| Audio Input      | Line In L/R                                    | Audio Output    | Headphone, Optic SPDIF |
| External Control | RS232(DE-9F), Ethernet(RJ45),<br>Service(RJ12) | External Sensor | RJ12                   |

Mechanical

|                            |                    |                            |                      |
|----------------------------|--------------------|----------------------------|----------------------|
| Product Dimensions (WxDxH) | 1455 x 71 x 834 mm | Package Dimensions (WxDxH) | 1650 x 207 x 1042 mm |
| Product Weight             | 29 kg              | Package Weight             | 40 kg                |
| Vesa Mounting              | 600 x 400 mm       | Bezel Width                | B:13   T/L/R:10 mm   |

Ingurumen Baldintzak

|                       |        |                    |        |
|-----------------------|--------|--------------------|--------|
| Operating Temperature | 0-40°C | Operating Humidity | 10-90% |
|-----------------------|--------|--------------------|--------|

Boterea

|              |                              |
|--------------|------------------------------|
| Power Supply | 110 VAC - 240 VAC - 50/60 Hz |
|--------------|------------------------------|

Energia-kontsumoa

|         |      |              |        |
|---------|------|--------------|--------|
| Typical | 187W | Deep Standby | ≤0.5 W |
|---------|------|--------------|--------|

Features

|               |                                                                                                                                                                                                                                                                                           |                     |                                                                                                      |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------|
| Main Features | Open Content Management Support,<br>Scheduler, USB-Autoplay, Auto-<br>Launch, HDMI-CEC, HDMI-Wakeup,<br>Auto-switch on Failover, Panel Lock,<br>OSD Rotation, NoSignalPowerOff,<br>Screen Saver, Pixel shift, Scheduler,<br>Videowall support, remote control<br>via LAN, Real Time Clock | Mechanical Features | Joystick, Cable Holder, OPS<br>Compatible, SDM Support, Internal<br>USB Cover, Detachable Power Plug |
| Speaker       | 2 x 10 W                                                                                                                                                                                                                                                                                  |                     |                                                                                                      |

Osagarria

|          |                                                                                              |
|----------|----------------------------------------------------------------------------------------------|
| Standard | QSG, IB, Power Cord, Remote<br>Control Unit, RC Battery, Mounting<br>Kit, Extension Brackets |
|----------|----------------------------------------------------------------------------------------------|

Ziurtapena

|        |     |     |     |
|--------|-----|-----|-----|
| Safety | YES | EMC | YES |
| CE     | YES |     |     |