

Digital Signage Displays

UHM86SH80B/4

VESTEL




Key Features



HDMI Wake Up

Kanpoko bideoa erabiltzen duzun bitartean erabiltzailearen esperientzia maximizatzeko multimedia-erreproduzitzailerak, pantaila kontrolatzaileak edo ordenagailuak bezalako gailuak, gure guztiak gailuek HDMI Wakeup funtzioa dute aktibatze/desaktibatze/ prest bistaratu HDMI kablea konektatu/deskonektatuz.



Pixel Shifting

Pixel Shifting is designed to be activated inside the SoC in order to prevent for potential risk of image sticking, caused by constant content. With this feature turned on, pixels on the screen will move in an interval while causing no interference of visual experience.



DAP (Dolby Audio Processing) Teknologia

Gure pantailak soinu errendimendu osoa eskaintzen dute Dolby-ren azken teknologia DAP erabiliz. Txertatuarekin DAP Teknologia, soinuaren errendimendu handiagoa lortzen du audio berdinketa adimenduna, elkarrizketa-hobekuntzak eta inguratzailea soinu nahasketa.




Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



Scheduler

Digital Signage Monitor Software allows many important features such as Scheduler. Scheduler sets your display turn on/off time easily and lets you not to worry about the status of your displays in any time.



HDR10 & 4K HDMI @60Hz

HDR10 bateragarritasunari esker, bezeroek hori guztia berma dezakete nabarmendutako edukiak HDR jarraibideak betetzen ditu eta goi-mailako mailara iristen da irudiaren kalitatea ahalik eta argi eta distiratsuena. Desberdina merkatuan dauden produktu asko baino, 4K edukia HDMI bidez iturria 60Hz-tan onartzen da.

Bistaratztea

Screen Size	86"	Backlight Type	Edge-Type LED
Brightness (typical)	400 cd/m²	Native Resolution	UHD: 3840 x 2160 - HDR10
Contrast Ratio (typical)	1200:1	Dynamic Contrast Ratio	40000:1
Panel Life Time (Min.)	30000 Hrs	Response Time (typical)	8 ms
Active Area (H x V)	1895 x 1066 mm	Pixel Pitch (H x V)	0.4935 x 0.4935 mm
PPI (pixel per inch)	52	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	1.07 B (10-bit)	Screen Treatment	2H
Haze Level	3%	Refresh Rate	60 Hz
Front Type	SNB	Orientation	Horizontal
Operation Hours	16/7	Area of Usage	Indoor

Sistema integratua

Mainboard Model	17MB135VS
-----------------	-----------

Atzeko I/Oak

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	4xHDMI2.0, 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Mechanical

Product Dimensions (WxDxH)	1975 x 103 x 1146 mm	Package Dimensions (WxDxH)	2163 x 318 x 1405 mm
Product Weight	65.8 kg	Package Weight	85.6 kg
Vesa Mounting	600 x 400 mm - M6	Bezel Width	B:38 T:38 L/R:38 mm

Ingurumen Baldintzak

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

Boterea

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Energia-kontsumoa

Typical	254 W	Deep Standby	≤0.5 W
---------	-------	--------------	--------

Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, remote control via LAN, Real Time Clock	Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance	Speaker	2 x 12 W

Osagarria

Standard

QSG, IB, Power Cord, Remote
Control Unit, RC Battery, Mounting
Kit, Extension Brackets, IR Extender
Cable

Ziurtapena

Safety	YES	EMC	YES
CE	YES		