



Key Features



Cefnogaeth Cyffwrdd

Mae ein sgriniau cyffwrdd yn gydnaws â'r gyfres hon. Mae Sgriniau Cyffwrdd Isgoch (IR) wedi'u cynllunio i arfogi'ch cynnyrch cyfredol â rhyngweithedd defnyddiwr gan ganiatáu i'r arddangosfa fod yn arddangosfa glyfar a llawer o gymwysiadau rhyngweithiol i'w mwynhau gan y defnyddwyr terfynol.

Arddangos

Screen Size	55"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	400 cd/m²
Native Resolution	1920 x 1080 (16:9) - FHD	Contrast Ratio (typical)	1200:1
Dynamic Contrast Ratio	40000:1	Panel Life Time (Min.)	30000 Hr
Response Time (typical)	6 ms	Active Area (H x V)	1210 x 681 mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	16.7 M (8-bit)
Screen Treatment	3H	Haze Level	1%
Refresh Rate	60 Hz	Front Type	Black Super Narrow Bezel
Orientation	Horizontal	Operation Hours	16/7
Area of Usage	Indoor		

System Adeiledig

Mainboard Model	17MB120DSR3-DSOPT3
-----------------	--------------------

I/Os cefn

RGB Input	Dsub 15 PIN VGA CON., YPbPr	RGB Output	N/A
Video Input	1xHDMI2.0, DP1.2a, DVI, 1xUSB3.0, 1xUSB2.0, 1xUSB2.0(USB cover)	Video Output	DP1.2a
Audio Input	LINE IN JACK	Audio Output	LINE OUT JACK
External Control	RS232(DSUB 9P), RJ12, Ethernet	External Sensor	N/A

Rhyngweithedd Cyffwrdd

Type of Touch Technology	Infrared (IR) Technology	Continuous Touch Points	10 Points
Sensitivity	Any touch with finger, gloved hand or pointer	Connectivity	HID, TUIO, Flash
Compatibility	Windows®7, Windows®8, Windows®10, Vista, XP, Mac® OS, Linux, Android	Orientation	Landscape support
Calibration	No need	Accuracy	%90
Reporting Rate	Up to 450 fps	Glass Type	Anti Glared (AG), 4mm Tempered
Frame Rate	up to 450 fps	Communication	USB 2.0
Power Supply Mode	USB	Supply Voltage	DC 5V +/- 5%
Average Current	400mA	Response Time	10ms
Touch Accuracy	+/-2mm (over 90% area)	Touch Durability	Unlimited
HID Compatibility	Yes USB	Object Sizes for Touch	5mm

Mechanical

Product Dimensions (WxDxH)	1280 x 123 x 751 mm	Package Dimensions (WxDxH)	1480 x 265 x 930 mm
Product Weight	29.45 kg	Package Weight	38.15 kg
Vesa Mounting	400 x 200 mm	Bezel Width	B:34 T:34 L/R:34 mm

Amodau Amgylcheddol

Operating Temperature	+40°C / 0°C	Operating Humidity	90%
-----------------------	-------------	--------------------	-----

Grym

Power Supply	110 VAC - 240 VAC
--------------	-------------------

Defnydd Pŵer

Typical	83 W	Deep Standby	≤0.5W
---------	------	--------------	-------

Features

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock	Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance	Speaker	2 x 8 W

Affeithiwr

Standard	QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable
----------	--

Ardystiad

Safety	YES	EMC	YES
CE	YES	Reability Approval	YES