

IFM75TH653/4




Key Features



Escrita suave simultânea Multi-Touch

O suporte de toque de 10 pontos detecta vários pontos de toque, aumentando a possibilidade de trabalho colaborativo. As telas também proporcionam uma experiência de escrita precisa e fácil de utilizar com o seu superfície lisa.



HDR10 & 4K HDMI @60Hz

Displays supporting HDR10 allows HDR based content to be shown, giving a brighter and more dynamic picture. This is further enhanced due to the support of 4K 60Hz, allowing ultra sharp, smooth Video content to be presented.



Vidro temperado anti-reflexo

Evita o reflexo da luz e proporciona um toque suave desempenho com tecnologia anti-reflexo. Design robusto com material de vidro temperado para evitar qualquer dano na tela



Colabore, anote com Oktopus

Colabore: visualize aulas, responda, compartilhe apontamentos e tome notas utilizando qualquer tablet ou portátil Antate: funciona no conteúdo do browser e em aplicações existentes Sondagem: coloque questões e obtenha feedback imediato dos participantes, exibindo os resultados instantaneamente.

Mostrar

Screen Size	75"	Panel Technology	IPS
Backlight Type	Direct-Type LED	Brightness (typical)	400 cd/m²
Native Resolution	UHD: 3840 x 2160 - HDR10	Contrast Ratio (typical)	1200:1
Dynamic Contrast Ratio	40000:1	Panel Life Time (Min.)	30000 Hrs
Panel Life Time (Average)	8 ms	Active Area (H x V)	1650 x 928 mm
Pixel Pitch (H x V)	0.429 x 0.429 mm	PPI (pixel per inch)	59
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07 B (10-bit)
Screen Treatment	2H	Haze Level	8%
Refresh Rate	60 Hz	Front Type	Touch Bezel Type
Orientation	Horizontal	Operation Hours	16/7 Panel
Area of Usage	Indoor		

Sistema integrado

Mainboard Model	17MB135VS
-----------------	-----------

E/S traseiras

RGB Input	VGA(DE-15F)	RGB Output	N/A
Video Input	4xHDMI2.0, 2xUSB2.0, USB2.0(Internal)	Video Output	HDMI2.0
Audio Input	Line In L/R	Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Interatividade por toque

Type of Touch Technology	Infrared (IR) Technology	Continuous Touch Points	10 Points
Sensitivity	Any touch with finger, gloved hand or pointer	Connectivity	HID, TUIO, Flash
Compatibility	Windows®7,Windows®8, Windows®10, Vista, XP, Mac® OS, Linux, Android	Orientation	Landscape support
Calibration	No need	Accuracy	%90
Reporting Rate	Up to 450 fps	Glass Type	Anti Glared (AG), 4mm Tempered
Frame Rate	up to 450 fps	Communication	USB 2.0
Power Supply Mode	USB	Supply Voltage	DC 5V +/- 5%
Average Current	400mA	Response Time	10ms
Touch Accuracy	+/-2mm (over 90% area)	Touch Durability	Unlimited
HID Compatibility	Yes USB	Object Sizes for Touch	5mm

Mechanical

Product Dimensions (WxDxH)	1731 x 119 x 1008 mm	Package Dimensions (WxDxH)	1990 x 265 x 1227 mm
Product Weight	58.3 kg	Package Weight	72.3 kg
Vesa Mounting	600 x 400 mm	Bezel Width	B:38 T:38 L/R:38 mm

Condições ambientais

Operating Temperature	+40°C / 0°C	Operating Humidity	90%
-----------------------	-------------	--------------------	-----

Poder

Power Supply	110 VAC - 240 VAC
--------------	-------------------

Consumo de energia

Typical	240 W	Maximum	320 W
Deep Standby	≤0.5W		

Features

Main Features	USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up	Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance	Speaker	2 x 12 W

Acessório

Standard	QSG, IB, Power Cord, Remote Control Unit, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable		
----------	--	--	--

Certificação

Safety	YES	EMC	YES
CE	YES	Reability Approval	YES