

## PD49U01



### Key Features



#### Auto Launch

We have made it easy to give any HTML5-based application link to the display within the SoC software. Upon this, the display will start with the given link. The application can either be an offline or an online application, allowing the customers to execute their own application.



#### Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.




#### Operation Time Support

Professional Panels used with this series are quality confirmed to operate 24 hours a day without any issues. Our customers will experience the highest quality of our screens unlimited to any operation. Upon this, the series come with 400 Nits brightness levels suitable for medial indoor environment.



#### Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



#### Pixel Shifting

Pixel Shifting is designed to be activated inside the SoC in order to prevent for potential risk of image sticking, caused by constant content. With this feature turned on, pixels on the screen will move in an interval while causing no interference of visual experience.



#### Image Orientation

SoC Software lets you choose the orientation of the display menu easily. This feature is important for portrait usage of our professional panel monitors.

## Display

|                         |  |                          |                       |
|-------------------------|--|--------------------------|-----------------------|
| Screen Size             | 49"  | Panel Technology         | IPS                   |
| Backlight Type          | Edge-Type LED                                      | Brightness (typical)     | 400 cd/m <sup>2</sup> |
| Native Resolution       | 1920 x 1080 (16:9) - FHD                           | Contrast Ratio (typical) | 1000:1                |
| Dynamic Contrast Ratio  | 40000:1  | Panel Life Time ( Min. ) | 50000 Hrs             |
| Response Time (typical) | 6 ms   | Active Area (H x V)      | 1054 x 593 mm         |
| Pixel Pitch (H x V)     | 0.5593 x 0.5593 mm                                 | PPI (pixel per inch)     | 45                    |
| Viewing Angle           | 178° Vert., 178° Hor.<br>(89U/89D/89L/89R) @ CR>10 | Color Value              | 16.7 M (8-bit)        |
| Screen Treatment        | 3H   | Haze Level               | 1%                    |
| Refresh Rate            | 60 Hz  | Front Type               | Ultra Narrow Bezel    |
| Orientation             | Horizontal / Vertical                              | Operation Hours          | 24/7                  |
| Area of Usage           | Indoor   |                          |                       |

## Built-in System

|                 |                    |
|-----------------|--------------------|
| Mainboard Model | 17MB120DSR3-DSOPT2 |
|-----------------|--------------------|

## Rear I/Os

|                  |  |                 |               |
|------------------|--|-----------------|---------------|
| RGB Input        | Dsub 15 PIN VGA CON., YPbPr                | RGB Output      | N/A           |
| Video Input      | 2xHDMI2.0, DP1.2a, DVI, 1xUSB3.0, 1xUSB2.0 | Video Output    | DP1.2a        |
| Audio Input      | LINE IN JACK                               | Audio Output    | LINE OUT JACK |
| External Control | RS232(DSUB 9P), RJ12, Ethernet             | External Sensor | N/A           |

## Mechanical

|                            |                    |                            |                         |
|----------------------------|--------------------|----------------------------|-------------------------|
| Product Dimensions (WxDxH) | 1100 x 66 x 636 mm | Package Dimensions (WxDxH) | 1195 x 145 x 775 mm     |
| Product Weight             | 14.15 kg           | Package Weight             | 17.6 kg                 |
| Vesa Mounting              | 200 x 200 mm       | Bezel Width                | B:17   T:10   L/R:10 mm |

## Environmental Conditions

|                       |        |                    |        |
|-----------------------|--------|--------------------|--------|
| Operating Temperature | 0-40°C | Operating Humidity | 10-90% |
|-----------------------|--------|--------------------|--------|

## Power

|              |                              |
|--------------|------------------------------|
| Power Supply | 110 VAC - 240 VAC - 50/60 Hz |
|--------------|------------------------------|

## Power Consumption

|         |      |              |        |
|---------|------|--------------|--------|
| Typical | 63 W | Deep Standby | ≤0.5 W |
|---------|------|--------------|--------|

## Features

|               |  |                     |   |
|---------------|--|---------------------|---|
| Main Features | Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock | Mechanical Features | Mechanical Buttons, IR Extender Support |
| Speaker       | 2 x 10 W   |                     |   |

## Accessory

|          |   |
|----------|---|
| Standard | QSG, IB, Remote Control, RC Battery, Mounting Kit |
|----------|---|

## Certification

|        |     |     |     |
|--------|-----|-----|-----|
| Safety | YES | EMC | YES |
| CE     | YES |     |     |