




Key Features



Usb Segurtasuna

Serie honek zure USBa eta zure edukia pantailaren atzeko estalkian babesteko aukera ematen du. Estalkia torloju batekin babestuta dago, kanpoko esku-hartzerik onartzen ez duena.




Usb erreprodukzio automatikoa

Argazki eta bideo edukia automatikoki erakutsi ahal izango duzu USB Auto-erreprodukzio funtzioarekin. SoC softwareak USB automatikoki erreproduzitzeko funtzioa aktibatzeke aukera ematen dizu, azken erabiltzaileei errazago erakusteko edozein multimedia pantailan eta beste ezertaz kezkatu gabe.



Diseinu sotila

Serie honen pantailak bezel ultra estuaren diseinua erakusten dute, ikusizko soberanak ezabatuz, ikusleek zure iragarkitako edukira bideratuz. Serie hau desiragarria da gure seinale digitalaren pantailen artean duen sakontasun meheenagatik.



SoC edukien kudeaketa

quad core SoC (System on Chip) batekin, serieko pantailak seinaleztapen digitalaren monitoreak dira lineaz kanpoko diseinatutako edukietarako eta hodeian oinarritutako kudeatutako edukietarako. Horrek zure eduki digitala pantailetan bistaratzen laguntzen du edukiak kudeatzeko sistemek.



Antolatzailea

Digital Signage Monitor Software-k funtzio garrantzitsu asko ahalbidetzen ditu, hala nola Scheduler. Scheduler-ek zure pantaila pizteko/itzaltzeko ordua erraz ezartzen du eta zure pantailen egoeraz ez kezkatzeko aukera ematen du edozein unetan.



Pixel-aldaketa

Pixel Shifting funtzioa aktibatu daiteke, eduki estatikoa denbora luzez bistaratzen denean irudiak itsasteko arriskua murrizteko. Ezaugarriak aldi-aldi pantailako irudia aldatzen du, ikusmen-esperientziaren interferentziarik eragin gabe.

Bistaratzea

Screen Size	65"	Panel Technology	IPS
Backlight Type	Slim DLED	Brightness (typical)	500 cd/m²
Native Resolution	3840 x 2160 (16:9) - UHD	Contrast Ratio (typical)	1200:1 (typ.)
Dynamic Contrast Ratio	50000:1	Panel Life Time (Min.)	50000 Hrs
Response Time (typical)	8 ms	Active Area (H x V)	1428.5 (H) × 803.5 (V) mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07G (8bits + FRC)
Color Gamut	72% NTSC	Haze Level	1%
Refresh Rate	60 Hz	Orientation	Landscape / Portrait
Operation Hours	24/7	Area of Usage	Indoor

Sistema integratua

Mainboard Model	17MB400VS	Operating System	Custom OS (built on Android AOSP)
Memory	2 GB DDR4	Storage	16 GB eMMC
Additional Storage	Micro SD (up to 1TB)	CPU	Quad-Core ARM Cortex-A55
GPU	ARM Mali-G31 MP2	Wired	10/100 Mbps Ethernet, IEEE 802.1X Authentication
WiFi	WiFi 5 (802.11 a/b/g/n/ac), IEEE 802.1X Authentication	Bluetooth	BT 5.1
HTML5 Browser	Vewd	Wireless Display	Miracast

Atzeko I/Oak

Video Input	4xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0	Video Output	1xHDMI2.0
Audio Output	Headphone, Optic SPDIF	External Control	RS232 (3.5mm jack green), Fast Ethernet (RJ45), Service (RJ12)
External Sensor	RJ12		

Mechanical

Product Dimensions (WxDxH)	1456 x 74 x 834 mm	Package Dimensions (WxDxH)	1650 x 190 x 997 mm
Product Weight	24.7 kg	Package Weight	34.75 kg
Vesa Mounting	600 (W) x 400 (H) mm M6	Bezel Width	B: 14 mm, T/L/R: 10 mm

Ingurumen Baldintzak

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

Boterea

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Energia-kontsumoa

Typical	134 W	Maximum	220 W
Deep Standby	≤0.5 W		

Features

Main Features	HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, SNMP	Mechanical Features	Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover
	Speaker		2x10 W

Osagarria

Standard	QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable				
----------	---	--	--	--	--

Ziurtapena

Safety	Yes	EMC	Yes
CE	Yes		