




Key Features




Android 13

Experience the extraordinary capabilities of Android 13 as it elevates our Interactive Flat Panel Displays to new heights.



Streamlined Design

Unleash the power of simplicity with our cutting-edge Interactive Flat Panel display, featuring a sleek and streamlined design that effortlessly blends into any environment, providing a distraction-free interface for seamless collaboration and captivating visual experiences.



Zero Bonding

Experience crystal-clear visuals and unparalleled touch responsiveness with our Interactive Flat Panel display, featuring cutting-edge zero bonding technology that eliminates distracting gaps between the screen and touch layer, creating a seamless and immersive viewing experience.

Arddangos

Brightness before cover glass (nits)	450 cd/m²	Brightness after cover glass(nits)	400 cd/m²
Screen Size	86"	Panel Technology	IPS
Backlight Type	LED Math Uniongyrchol	Native Resolution	UHD: 3840 x 2160 HDR10
Aspect Ratio	16:9	Contrast Ratio (typical)	1200:1
Dynamic Contrast Ratio	35000:1	Life Time (typical)	50000 Hrs
Response Time (typical)	8 ms	Active Area (H x V)	1895 x 1066 mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	Color Value	1.07 B (8-bit+2bit FRC)
Haze Level	8%	Refresh Rate	60 Hz
Glass Type	Gwrth-lacharedd Tymherus 3 mm	Glass Hardness	7H

System Adeiledig

Mainboard Model	MB460VS	Operating System	Android 13 OS (Google)
Memory	8 GB DDR4	Storage	64 GB EMMC
CPU	CA55 Quad core	GPU	ARM Mali-G52 MP2 GPU
Wired	LAN: 10/100/1000 Mbps	WiFi	2T2R 802.11a/b/g/n/ac, 2.4/5Ghz
Bluetooth	BT 5.0		

I/Os cefn

Touch Output	2 x USB-B	Video Input	3 x HDMI2.0 (HDCP2.2), OPS Slot
Video Output	1 x HDMI2.0 (Allbwn Daisychain)	Audio Output	1 x Clustffon (Allbwn llinell), 1 x SPDIF Optig
External Control	1 x RJ45 (Gorchmynion LAN), 1 x jac 3.5mm (Gorchmynion RS232), 1 x RJ12 (Blwch Synhwyrdd), 1 x RJ12 (Mewnbwn Gwasanaeth)	USB	2 x USB-A (3.0), 1 x USB-C

Hygyrchedd Blaen

Console Buttons	Pŵer ymlaen/i ffwrdd	IR Receiver	Ie
-----------------	----------------------	-------------	----

Rhyngweithedd Cyffwrdd

Type of Touch Technology	Infrared (IR) Technology	Scan Rate	> 125Hz
Continuous Touch Points	Uchafswm o 20 pwynt cyffwrdd* *Wedi'i gyfyngu gan derfynau'r rhaglen	Touch Resolution	32768 x 32768 px
Sensitivity	Unrhyw gyffyrddiad â bys, llaw â maneg neu bwyntydd	Compatibility	Windows®, Mac® OS, Linux, Android
Response Time	8 ms	Touch Accuracy	+/- 1 mm (over 90% area)
Pen Type	Pen di-fatri	Pen Identities	Cymorth 2-gyffwrdd
Object Sizes for Touch	min. 2mm & min. 8 mm		

Mechanical

Product Dimensions (WxDxH)	1959x 87 x 1140 mm	Package Dimensions (WxDxH)	2105 x 265 x 1300 mm
Product Weight	62 kg	Package Weight	77 kg
Vesa Mounting	800 x 600 mm - M8	Bezel Width	Gwaelod: 24 Uchaf: 14 Chwith/Dde: 14 mm

Amodau Amgylcheddol

Operating Temperature	+40°C / 0°C	Storage Temperature	+60°C / -10°C
Storage Humidity	90% / 10%	Operating Humidity	90% / 10%

Grym

Power Supply	110-240V 50-60Hz	Energy Label	Dosbarth F
--------------	------------------	--------------	------------

Defnydd Pŵer

Typical	158 W - SDR 358 W - HDR	Maximum	400 W
Deep Standby	0.38 W		

Nodweddion Mecanyddol

Rear Ports	1e	Bottom Ports	1e
Side Ports	1e	Logo	1e ar y Plât Logo
Speakers	1e - 2x20W	Sensors	Ar gael gyda Blwch Synhwyrdd allanol
Detachable power cable	1e	Carrying slots/handles	1e (x2)
OPS Slot	1e		

Ategolion

Information Booklet	Ydw (Llawlyfr Defnyddiwr + Canllaw Cychwyn Cyflym)	Remote Control Unit	1e (x1)
Pens	Pennau Magnetig (x2)	Power cable	1e (datodadwy)

Nodweddion Meddalwedd

Applications	Vestel Launcher, Vdraw, Eshare, Officesuite, AquaMail, Chromium, Rheolwr Ffeiliau, Chwaraewr Cyfryngau, Rheolwr Ffeiliau Cwmwl		
--------------	--	--	--

Ardystiad

Safety	1e	UKCA	1e
EMC	1e	CE	1e